




GYTS GYTA Fiber Optic Cable Armoured 12 24 48 96 Core For Duct

Our Product Introduction

for more products please visit us on fiberoptical-cables.com


Basic Information

- Place of Origin: GUANGZHOU/CHINA
- Brand Name: PUNAI SGD/CABLEPULS
- Certification: ISO/CE/ROSH
- Model Number: GYTS
- Minimum Order Quantity: 2km
- Packaging Details: Wooden Spool /drum
- Delivery Time: 5-25days
- Payment Terms: 30%TT as deposit,70%Balance before shipping.
- Supply Ability: 100km





Product Specification

- Warranty Period: 25 Years
- Jacket Color: Black
- Jacket Material: PE/LSZH
- Fiber Type: G.652D
- Crush Resistance: Long Term: 300N/100mm, Short Term: 1000N/100mm
- Tensile Strength: Long Term: 600N, Short Term: 1500N
- Storage Temperature: -40°C To +70°C
- Outer Jacket Material: HDPE
- Cable Color: Black
- Cable Diameter: 12.5 Mm
- Armored Type: Steel Tape/Aluminum
- Application: Outdoor Duct Installation
- Fiber Count: 24/48/96/144/288
- Highlight: Armoured Fiber Optic Cable, GYTS GYTA



More Images



Product Description

Wholesale Best Selling Armoured Cable GYTS GYTA 12 24 48 96 Core Fiber Optic Cable For Duct

Characteristics:

·Steel jacket offers high tension and crush resistance special gel in the tube offers critical protection for the fibers
·With steel central strength member ·PE jacket itself prevents UV, and UV material can be added ·to perform much better It's available under high and low temperatures ·anti-aging



Applications:

·Conduit/buried ·Connecting communication equipments ·Multi-cores wiring systems in data centers


Standard:

·GYTS complies with YD/T901-2009 and IEC 60794-1 standards ·YD/T 901-2009 & IEC 60794-1

Our Product Introduction



GYTS Cable Place Order Information



CABLE DATA

Cable Type	Fiber Count	Strand ed units	Cable Diame ter (mm)	Cabl e Weig ht (kg/k m)	Bending Radius Dynamic/St atic (MM)	Tensile Strength Long/Short Term (N)	Crush Resistance Long/Short Term (N/100 mm)
GYTA≤60	≤60	5	9.8	108	20D/10D	240/800	300/1000
GYTA-62~72	62~72	6	10.4	129	20D/10D	300/850	300/1000
GYTA-74~96	74~96	8	10.6	132	20D/10D	350/1200	300/1000
GYTA-98~120	98~120	10	12.1	161	20D/10D	450/1400	300/1000
GYTA-122~144	122~144	12	13.6	198	20D/10D	700/2000	300/1000

Fiber Parameters


No.	Items	Unit	Specificati on
1	Mode Field Diameter	1310nm 1550nm	μm 9.2±0.4 10.4±0.8
2	Cladding Diameter	μm	125.0±1.0
3	Cladding Non-Circularity	%	≤1.0
4	Core-Cladding Concentricity Error	μm	≤0.5
5	Coating Diameter	μm	245±5
6	Coating Non-Circularity	%	≤6.0
7	Cladding-Coating Concentricity Error	μm	≤12.0
8	Cable Cutoff Wavelength	nm	λ _c ≤1260
9	Attenuation(max.)	1310nm 1550nm 1380nm 1625nm	dB/km ≤0.35 ≤0.21 ≤0.35 ≤0.24
10	Attenuation and wavelength	1310nm 1285-1330nm 1550nm 1525-1575nm 1550nm 1480-1580nm	dB/km ≤0.04 ≤0.03 ≤0.05
		1288-1339nm	ps/(nm.km) ≥-3.5, ≤3.5

11	Dispersion	1271-1360nm	ps/(nm.km)	≥-5.3, ≤5.3
		1480-1580nm	ps/(nm.km)	≤20
		1550nm	ps/(nm.km)	≤18
12	Zero dispersion wavelength		Nm	1300-1324
13	Zero dispersion slope		ps/(nm ² ·km)	≤0.092
14	Typical value		ps/(nm ² ·km)	0.04
15	Largest individual fiber		Ps/√ km	0.2
16	Link design values		Ps/√ km	0.1
17	Two way average		1310nm-1550	≤0.01dB

Cable Marking&Fibers Colors

COMPANY Fiber cable name N*cores G.652D 2024 XXXXm
*The marking is printed every 1 meter;
**"G.652D" means ITU-T Rec. Low Water Peak (LWP) G.652 single mode optical fiber..

Also can according to client cable marking.



Production Supplier Profile



COMPANY PROFILE



ABOUT FIBER
Guangzhou fiber cablepuls co.,ltd

Fiber cablepuls is one of the high-tech fiber optic cable factories in China that can produce the most complete series of fiber optic cables, equipped with the most advanced fiber optic cable manufacturing, and have the most advanced fiber optic connector production and testing equipment in China.

The factory has obtained ISO 9001:2015, ISO 14001:2004 and GB/T28001:2001 successively obtained international system certification.

Over the past 12 years, we have provided optical cable products and comprehensive solutions to more than 90 countries and regions around the world, and have received unanimous praise from customers, such as foreign telecom departments of the United States, Mexico Telecom, Thailand Telecom, Philippines Telecom, etc.; domestic customers include China Mobile, the General Administration of Radio, Film and Television, Lenovo, and many other large national enterprises.


**guangzhou
fiber
cablepuls
co ltd**

+8613687956390 cotton@fibercabl



OUR PRODUCTION CAPACITY AND QUALITY CONTROL SYSTEM



How do I place an OEM or customized order?

- 1) Send your purchase intention to our email: cotton@fibercablepuls.com
- 2) Our sales team will contact you to confirm the product specification, packaging, printing, quantity, and other specific information.
- 3) Sign the contract or Proforma Invoice.
- 4) After receiving your deposit, we will start to arrange the production.
- 5) 2 weeks before the completion of production, we will notify you to start contacting shipping.

925-926, Building B1, No. 2 Chuanghui Avenue, Yonghe Yushan InternationalGuangzhou city,Guangdong province,China