ġ.

more products please visit us on fiberoptical-cables.com

Outdoor Singlemode Overhead Armored Fibre Optical Cable Gyxtw 2 4 6 8 12 24 Core Fiber Optic Cable

Basic Information

• Place of Origin: GUANGZHOU/CHINA • Brand Name: PUNAISGD/CABLEPULS · Certification: ISO/CE/ROSH

GYXTW Model Number: Minimum Order Quantity: 2km

Packaging Details: Wooden Spool /drum

Delivery Time: 5-25days

30%TT as deposit,70%Balance before • Payment Terms:

shipping.

100km Supply Ability:



Product Specification

Armored Tape: Steel Tape

• Cable Model: GYXTW Fiber Optic Cable • Construction: Central Loose Tube • Structure: Loose Tube Warranty Time: 25 Yes

 Manufacturer: • Fiber Range: 4-24 • Loose Tube Material:

PBT(high Quality • Highlight: Armored Fiber Optic Cable,

Armored Outdoor Fiber Cable, Overhead Armored Fiber Cable



More Images








Product Description

Outdoor Singlemode Overhead Armored Gyxtw 4 6 8 12 Core Fiber Optic Cable

which is made of high modulus plastic materials and filled with filling compound. Two parallel steel wires are placed at both sides of the cable core while Corrugated steel tape armor with PE sheath is extruded over it. and water-blocking materials are distributed into interstices between them to guarantee the compactness and longitudinal water-blocking performance.





Cable overall Diameter :7.0-8.0mm Fiber core/Wires:8 Core fiber Fiber type : Mulit mode OM3 Fiber

Fiber attenauation for 8 core loss:40.6dB/km@1300nm 8 Core Fiber color Identify: Blue Orange Green Brown Grey White Red Black Cable outer sheath: PE Material anti UV Black Color

Package length: 500M 1000M 2000 Meter in a Roll

Production time :3week/bulk order OEM/ODM:YES

Payment terms:T/T



Vary application and vary aerial /underground isntall way


Easy strip easy splicing when installation

Light weight easy for installation

Light armored provide anti rodent for Rice Bird Monkey

Affordable price lower Budget Save cost

GYXTW Cable Place Order Information



APPLICATION

Smart City Safe City Surveillance CCTV Camera System

Telephone. CATV, Fibre Broadband

Aerial / duct installation light anti rodent Rural networking telecommunication system

8Core Multi mode OM3 Fibre Local area networks (LAN) 1 & 10 & 40 & 100 & 400 Gb/s Ethernet

Fiber count	Structur	Fibers per tube	Loose tube diameter (mm)	CSM diameter/p ad diameter (mm)	Nominal Thicknes s of outer jacket (mm)	Cable diameter/ Height (mm)	Cable weight (kg/km)
2	1	2	1.7±0.1	1.0/1.0	1.6	8.0±0.2	57

4	1	4	1.85±0.1	1.0/1.0	1.6	8.0±0.2	58	
6	1	6	1.9±0.1	1.0/1.0	1.6	8.0±0.2	58	
8	1	8	2.0±0.1	1.0/1.0	1.6	8.0±0.2	60	
12	1	12	2.2±0.1	1.0/1.0	1.6	8.0±0.2	60	

Fiber P	arameters			
No.	Items	Unit	Specificatio n G.652D	
1	Mode Field Diameter	μm	9.2±0.4	
l'	Wode Field Diameter	1550nm	μm	10.4±0.8
2 3	Cladding Diameter	•	μm	125.0±1.0
3	Cladding Non-Circularity		%	≤1.0
4	Core-Cladding Concentricity E	μm	≤0.5	
5	Coating Diameter		μm	245±5
6	Coating Non-Circularity		%	≤6.0
7	Cladding-Coating Concentricity	y Error	μm	≤12.0
8	Cable Cutoff Wavelength		nm	λcc≤1260
		1310nm	dB/km	≤0.35
		1550nm	dB/km	≤0.21
9	Attenuation(max.)	1380nm	dB/km	≤0.35
	Attendation(max.)	1625nm	dB/km	≤0.24
		1310nm 1285-1330nm	dB/km	≤0.04
10	Attenuation and	1550nm 1525-1575nm	dB/km	≤0.03
	wavelength	1550nm 1480-1580nm	dB/km	≤0.05
11		1288-1339nm	ps/(nm.km)	≥-3.5, ≤3.5
		1271-1360nm	ps/(nm.km)	≥-5.3, ≤5.3
	Dispersion	1480-1580nm	ps/(nm.km)	≤20
	Biopersion	1550nm	ps/(nm.km)	≤18
12	Zero dispersion wavelength		Nm	1300-1324
13	Zero dispersion slope		ps/(nm2•km)	≤0.092
14	Typical value		ps/(nm2•km)	0.04
15	Largest individual fiber		Ps/√ km	0.2
16	Link design values		Ps/√ km	0.1
17	Two way average		1310nm-1550	≤0.01dB

Steel wire 0.7x2 Loose tube :2.2mm Diameter:7.1



Cable Marking&Fibers Colors
COMPANY Fiber cable name N*cores G.652D 2024 XXXXm

*The marking is printed every 1 meter;
**"G.652D" means ITU-T Rec. Low Water Peak (LWP) G.652 single mode optical fiber..

Also can according to client cable marking.





guangzhou fiber cablepuls

cotton@fibercabl

O co ltd +8613687956390



OUR PRODUCTION CAPACITY AND QUALITY CONTROL SYSTEM





- How do I place an OEM or customized order?

 1) Send your purchase intention to our email: cotton@fibercablepuls.com

 2) Our sales team will contact you to confirm the product specification, packaging, printing, quantity, and other specific information.

 3) Sign the contract or Proforma Invoice.

 4) After receiving your deposit, we will start to arrange the production.

 5) 2 weeks before the completion of production, we will notify you to start contacting shipping.

925-926, Building B1, No. 2 Chuanghui Avenue, Yonghe Yushan InternationalGuangzhou city,Guangdong province,China