

Outdoor Optical Fiber Direct Buried Cable GYFTA53 Double Jacket For Underground

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Price:
- · Packaging Details:
- Delivery Time:
- Payment Terms:

PUNAISGD/CABLEPULS

CHINA

- ISO/CE/ROSH
- Minimum Order Quantity:

- Supply Ability:
- GYFTA53 2km negotiable wooden/ spool drum 5-25days 30%TT as deposit,70%Balance before shipping.



Product Specification

- Item No.:
- Armored:
- Armored Type:
- FACTORY:
- Fiber Type:
- Application:
- Highlight:

GYFTA53 Yes

100km

- **Double Armored**
- DIRECTLY FACTORY
- G.652D
- **Dicetly Buried**
- Direct Buried Cable GYFTA53, Optical Fiber Direct Buried Cable, **Underground Direct Buried Fiber Cable**



More Images





Outdoor Optical Fiber Cable GYFTA53 Double Jacket For Underground Direct Bury

GYFTA53 cable is a type of outdoor, armoured fiber optic cable designed for long-distance, high-capacity communication networks, It is commonly used in both aerial and underground installations.

The cable features a central tube design with stranded loose tubes and water-blocking gel. The loosetubes provide protection to the fibers and allow for easy installation and maintenance. The gel provideswater resistance, making the cable suitable for deployment in harsh environmental conditions.

GYFTA53 cable also features a corrugated steel tape armor, providing physical protection against rodentbites, moisture, and other external threats. This makes it ideal for use in areas where the cable is exposed to potential damage.

The cable is available in various fiber counts to meet different capacity requirements, and it can becustomized with different sheath materials for specific environmental conditions, such as UV resistance orfire retardancy.

Overall, GYFTA53 cable is a reliable and durable solution for long-distance, high-capacity fiber opticcommunication networks, offering excellent performance and protection in demandina outdoorenvironments.





-Sheath Steel tape -Inner sheath Water-blocking tape -Loose tube -Strength member sheath -Central strength member

Optical fiber Gel filling compound

Details Images



Product Paramenters

Fib er cou nt	Struct ure	Fibers per tube	Loose tube diameter(mm)	CSM diameter /pad diameter (mm)	Thickness of inner jacket (mm)	Thickness of outer jacket (mm)	Cable diameter (mm)	Cable Weight(kg/ km)
4	1+6	4	1.7+0.1	1.8/1.8	0.9 ± 0.1	1.8 ± 0.1	12.8 ± 0.5	164
6	1+6	6	1.7+0.1	1.8/1.8	0.9 ± 0.1	1.8 ± 0.1	12.8 ± 0.5	164
8	1+6	4	1.7+0.1	1.8/1.8	0.9 ± 0.1	1.8 ± 0.1	12.8 ± 0.5	164
12	1+6	6	1.7+0.1	1.8/1.8	0.9 ± 0.1	1.8 ± 0.1	12.8 ± 0.5	164
18	1+6	6	1.7+0.1	1.8/1.8	0.9 ± 0.1	1.8 ± 0.1	12.8 ± 0.5	165
24	1+6	6	1.7+0.1	1.8/1.8	0.9 ± 0.1	1.8 ± 0.1	12.8 ± 0.5	165
30	1+6	6	1.7+0.1	1.8/1.8	0.9 ± 0.1	1.8 ± 0.1	12.8 ± 0.5	166
36	1+6	6	1.7+0.1	1.8/1.8	0.9 ± 0.1	1.8 ± 0.1	12.8 ± 0.5	166
48	1+6	12	2.0+0.1	1.8/1.8	0.9 ± 0.1	1.8 ± 0.1	13.8 ± 0.5	191
60	1+6	12	2.0+0.1	2.0/2.0	0.9 ± 0.1	1.8 ± 0.1	13.8 ± 0.5	191
72	1+6	12	2.0+0.1	2.0/2.0	0.9 ± 0.1	1.8 ± 0.1	13.8 ± 0.5	192
84	1+7	12	2.0+0.1	2.0/2.0	0.9 ± 0.1	1.8 ± 0.1	14.7 ± 0.5	218
96	1+8	12	2.0+0.1	2.0/2.0	0.9 ± 0.1	1.8 ± 0.1	15.4 ± 0.5	234
108	1+9	12	2.0+0.1	2.0/2.0	0.9 ± 0.1	1.8 ± 0.1	16.1 ± 0.5	253
120	1+10	12	2.0+0.1	2.0/2.0	0.9 ± 0.1	1.8 ± 0.1	16.8 ± 0.5	272
132	1+11	12	2.0+0.1	2.0/2.0	0.9 ± 0.1	1.8 ± 0.1	17.4 ± 0.5	293
144	1+12	12	2.0+0.1	2.0/2.0	0.9 ± 0.1	1.8 ± 0.1	18.2 ± 0.5	317
288	1+9+1 5	12	2.0+0.1	2.0/2.0	0.9 ± 0.1	1.8 ± 0.1	20.1 ± 0.5	383

Learn more about our products and factory



The ractory has obtained Sk3 ISU-8007-2015, ISU-14007-2004 and Sk1/28007-2005 successive) obtained international system certification. Over the past 72 years, we have provided optical cable products and comprehensive solutions in more than 90 counties and regions around the work, and have receive unanimous praise from castomers, such as foreign telecom departments of the Unitor States, Moxico Telecom, Thailand Telecom, Philippines Telecom, etc., domestic cas tomes include: China Mobile, the General Administization of Radio, Triin and Television



OUR PRODUCTION CAPACITY AND QUALITY CONTROL SYSTEM



Color Fiber Testing

A Stranded Loose Tube

A Finished Cable Testing



HOT-SALE PRODUCT





FAQ

1. Why choose us?

We are manufacturer, Located in Guangzhou, China, started from 2011, sell to Domestic Market(100.00%). There are total about 11-50 people in our factory. 2. how can we guarantee quality? Always a pre-production sample before mass production; Always final Inspection before shipment; 3.Can you send products to my country? Sure, we can. If you do not have your own ship forwarder, we can help you. 4. Can you do OEM for me? We accept all OEM orders,just contact us and give me your design.we will offer you a reasonable price and make samples for you. 5. what services can we provide? Accepted Delivery Terms: FOB,CIF,EXW Accepted Payment Currency:USD,EUR,JPY,CAD,AUD,HKD,GBP,CNY,CHF; Accepted Payment Type: T/T,L/C,D/P D/A,PayPal,Western Union,Escrow; Language Spoken:English,Chinese

guangzhou fiber cablepuls co Itd							
+8613687956390	Cotton@fibercablepuls.com	© fiberoptical-cables.com					
925-926, Building B1, No. 2 Chu	anghui Avenue, Yonghe Yushan Inte province,China	rnationalGuangzhou city,Guangdong					