₫

more products please visit us on fiberoptical-cables.com

Duct Optical Cable GYTS 72 Cores Pipeline Armored Outdoor Fiber

Basic Information

• Place of Origin: GUANGZHOU/CHINA • Brand Name: PUNAISGD/CABLEPULS ISO/CE/ROSH · Certification:

 Model Number: GYTS-72B1.3

 Minimum Order Quantity: 2km • Price: negotiable

Packaging Details: Wooden Spool /drum

• Delivery Time: 5-25days

30%TT as deposit,70%Balance before • Payment Terms:

shipping. 100km Supply Ability:



Product Specification

• Item No.: GYTS-72B1.3 Armored Type: Steel Tape • Strength Member: Steel Wire • Fiber Type: Single Mode Jacket Material: PΕ

• Cable Diameter: 9.0±0.2 Mm

• Application: Outdoor Duct Installation

• Warranty Period: 25 Years


• Highlight: **Duct Optical Cable GYTS**, **Duct Optical Cable 72 Cores.**

Pipeline Outdoor Fiber Cables





More Images



Product Description

Duct Optical Cable GYTS 72 Cores Pipeline Armored Outdoor Fiber Cables


The structure of GYTS optical fiber cable 250µm fiber is positioned in a loose tube made of high modulus material, and the loose tube is filled with waterproof compound. The center of the cable core is a metallic steel wire strength member, for some cores fiber cable, a layer of polyethylene (PE) needs to be extruded outside the metallic steel wire central strength member. Tubes (and fillers) are stranded around the strength member into a compact and circular cable core. The corrugated steel tape is longitudinally applied over the cable core, which is filled with the filling compound to protect it from water ingress. The cable is completed with a PE sheath.


- Steel wire strength.filler protect tube fiber.steel tape armord.
- · Good ultra violet radiation resistant property
- · Good moisture-resistance.

Applications:


- Adopted to Outdoor distribution.
- Suitable for aerial .pipeline laying method.
 Long distance and local area network communication.

Our Product Introduction





GYTS Cable Place Order Information



CABLE DATA

Cable Type	Fiber Count	Strande	Cable Diamet er (mm)	Weigh	Radius Dynamic/Stati c	Strength Long/Short Term	Crush Resistance Long/Short Term (N/100 mm)
GYTA≤60	≤60	5	9.8	108	20D/10D	240/800	300/1000
GYTA-62~72	62~72	6	10.4	129	20D/10D	300/850	300/1000
GYTA-74~96	74~96	8	10.6	132	20D/10D	350/1200	300/1000
198~120	98~120	-	12.1	161	20D/10D	450/1400	300/1000
GYTA- 122~144	122~14 4	12	13.6	198	20D/10D	700/2000	300/1000

Fiber Parameters							
No.	Items	ems					
			G.652D				
1	Mode Field Diameter	1310nm	μm	9.2±0.4			
	Mode Field Diameter	1550nm	μm	10.4±0.8			
2	Cladding Diameter	μm	125.0±1.0				
3	Cladding Non-Circularity	%	≤1.0				
4	Core-Cladding Concentricity Erro	μm	≤0.5				
5	Coating Diameter	μm	245±5				
6	Coating Non-Circularity	%	≤6.0				
7	Cladding-Coating Concentricity E	μm	≤12.0				
8	Cable Cutoff Wavelength	Cable Cutoff Wavelength					
		1310nm	dB/km	≤0.35			
		1550nm	dB/km	≤0.21			
9	Attenuation(max.)	1380nm	dB/km	≤0.35			
	Attendation(max.)	1625nm	dB/km	≤0.24			
10		1310nm 1285-1330nm	dB/km	≤0.04			
	Attenuation and wavelength	1550nm 1525-1575nm	dB/km	≤0.03			
	Atteridation and wavelength	1550nm 1480-1580nm	dB/km	≤0.05			
		1288-1339nm	ps/(nm.km)	≥-3.5, ≤3.5			
		1271-1360nm	ps/(nm.km)	≥-5.3, ≤5.3			

	I	1480-1580nm	ps/(nm.km)	≤20
11	Dispersion	1550nm	ps/(nm.km)	≤18
12	Zero dispersion wavelength	Nm	1300- 1324	
13	Zero dispersion slope		ps/(nm2•km)	≤0.092
14	Typical value		ps/(nm2•km)	0.04
15	Largest individual fiber	Ps/√ km	0.2	
16	Link design values	Ps/√ km	0.1	
17	Two way average		1310nm-1550	≤0.01dB

Cable Marking&Fibers Colors

COMPANY Fiber cable name N*cores G.652D 2024 XXXXm

*The marking is printed every 1 meter;

****G.652D** means ITU-T Rec. Low Water Peak (LWP) G.652 single mode optical fiber..

Also can according to client cable marking.



Production Supplier Profile





+8613687956390 cotton@fibercabl



OUR PRODUCTION CAPACITY AND QUALITY CONTROL SYSTEM





- How do I place an OEM or customized order?

 1) Send your purchase intention to our email: cotton@fibercablepuls.com

 2) Our sales team will contact you to confirm the product specification, packaging, printing, quantity, and other specific information.

 3) Sign the contract or Proforma Invoice.

 4) After receiving your deposit, we will start to arrange the production.

 5) 2 weeks before the completion of production, we will notify you to start contacting shipping.

925-926, Building B1, No. 2 Chuanghui Avenue, Yonghe Yushan InternationalGuangzhou city,Guangdong province,China