



Fiber Optic GYTS Duct Cable Armoured Cable Underground GYTS GYTA 96 Core

Our Product Introduction

for more products please visit us on fiberoptical-cables.com


Basic Information

- Place of Origin: GUANGZHOU/CHINA
- Brand Name: PUNAISGD/CABLEPULS
- Certification: ISO/CE/ROSH
- Model Number: GYTS-96B1.3
- Minimum Order Quantity: 2km
- Price: negotiable
- Packaging Details: Wooden Spool /drum
- Delivery Time: 5-25days
- Payment Terms: 30%TT as deposit,70%Balance before shipping.
- Supply Ability: 100km



Product Specification

- Item No.: GYTS-96B1.3
- Armored Type: Steel Tape
- Strength Member: Steel Wire
- Jacket Material: PE
- Cable Diameter: 10.6±0.2 Mm
- Application: Pipeline
- Warranty Period: 25 Years
- Highlight: GYTS Duct Cable, Armoured Duct Cable, GYTS Duct Cable



More Images



Product Description

Duct Optical Cable GYTS Armoured Cable Underground GYTS GYTA 96 Core Fiber Optic Cable

The structure of GYTS optical fiber cable 250μm fiber is positioned in a loose tube made of high modulus material, and the loose tube is filled with waterproof compound. The center of the cable core is a metallic steel wire strength member, for some cores fiber cable, a layer of polyethylene (PE) needs to be extruded outside the metallic steel wire central strength member. Tubes (and fillers) are stranded around the strength member into a compact and circular cable core. The corrugated steel tape is longitudinally applied over the cable core, which is filled with the filling compound to protect it from water ingress. The cable is completed with a PE sheath.

Characteristics:

- Steel jacket offers high tension and crush resistance special gel in the tube offers critical protection for the fibers
- With steel central strength member ·PE jacket itself prevents UV, and UV material can be added ·to perform much better It's available under high and low temperatures ·anti-aging



Applications:

- Conduit/buried ·Connecting communication equipments ·Multi-cores wiring systems in data centers


Standard:

Our Product Introduction

· GYTS complies with YD/T901-2009 and IEC 60794-1 standards · YD/T 901-2009 & IEC 60794-1



GYTS Cable Place Order Information



CABLE DATA

Cable Type	Fiber Count	Stranded units	Cable Diameter (mm)	Cable Weight (kg/km)	Bending Radius Dynamic/Static (MM)	Tensile Strength Long/Short Term (N)	Crush Resistance Long/Short Term (N/100 mm)
GYTA≤60	≤60	5	9.8	108	20D/10D	240/800	300/1000
GYTA-62~72	62~72	6	10.4	129	20D/10D	300/850	300/1000
GYTA-74~96	74~96	8	10.6	132	20D/10D	350/1200	300/1000
GYTA-98~120	98~120	10	12.1	161	20D/10D	450/1400	300/1000
GYTA-122~144	122~144	12	13.6	198	20D/10D	700/2000	300/1000

Fiber Parameters


No.	Items	Unit	Specification
1	Mode Field Diameter	1310nm 1550nm	μm 9.2±0.4 10.4±0.8
2	Cladding Diameter	μm	125.0±1.0
3	Cladding Non-Circularity	%	≤1.0
4	Core-Cladding Concentricity Error	μm	≤0.5
5	Coating Diameter	μm	245±5
6	Coating Non-Circularity	%	≤6.0
7	Cladding-Coating Concentricity Error	μm	≤12.0
8	Cable Cutoff Wavelength	nm	λ _c ≤1260
9	Attenuation(max.)	1310nm 1550nm 1380nm 1625nm	dB/km ≤0.35 ≤0.21 ≤0.35 ≤0.24
10	Attenuation and wavelength	1310nm 1285-1330nm 1550nm 1525-1575nm 1550nm 1480-1580nm	dB/km ≤0.04 ≤0.03 ≤0.05
		1288-1339nm 1271-1360nm	ps/(nm.km) ≥-3.5, ≤3.5 ≥-5.3, ≤5.3

11	Dispersion	1480-1580nm	ps/(nm.km)	≤20
		1550nm	ps/(nm.km)	≤18
12	Zero dispersion wavelength	Nm		1300-1324
13	Zero dispersion slope	ps/(nm ² ·km)		≤0.092
14	Typical value	ps/(nm ² ·km)		0.04
15	Largest individual fiber	Ps/√ km		0.2
16	Link design values	Ps/√ km		0.1
17	Two way average	1310nm-1550		≤0.01dB


Cable Marking&Fibers Colors

COMPANY Fiber cable name N*cores G.652D 2024 XXXXm
*The marking is printed every 1 meter;
**"G.652D" means ITU-T Rec. Low Water Peak (LWP) G.652 single mode optical fiber..


Also can according to client cable marking.



Production Supplier Profile



COMPANY PROFILE




ABOUT FIBER

Guangzhou fiber cablepuls co.,ltd



Fiber cablepuls is one of the high-tech fiber optic cable factories in China that can produce the most complete series of fiber optic cables, equipped with the most advanced fiber optic cable manufacturing, and have the most advanced fiber optic connector production and testing equipment in China.

The factory has obtained SGS ISO9001:2015, ISO14001:2004 and GB/T28001:2001 successively obtained international system certification.

Over the past 12 years, we have provided optical cable products and comprehensive solutions to more than 50 countries and regions around the world, and have received unanimous praise from customers, such as foreign telecom departments of the United States, Mexico Telecom, Thailand Telecom, Philippines Telecom, etc.; domestic customers include: China Mobile, the General Administration of Radio, Film and Television, Lenovo, and many other large national enterprises.



guangzhou
fiber
cablepuls
co ltd

+8613687956390 cotton@fibercabl



OUR PRODUCTION CAPACITY AND QUALITY CONTROL SYSTEM



How do I place an OEM or customized order?

- 1) Send your purchase intention to our email: cotton@fibercablepuls.com
- 2) Our sales team will contact you to confirm the product specification, packaging, printing, quantity, and other specific information.
- 3) Sign the contract or Proforma Invoice.
- 4) After receiving your deposit, we will start to arrange the production.
- 5) 2 weeks before the completion of production, we will notify you to start contacting shipping.

925-926, Building B1, No. 2 Chuanghui Avenue, Yonghe Yushan InternationalGuangzhou city,Guangdong province,China