fibers

· Certification: ISO/CE/ROSH GJXH-1G657A Model Number:

Minimum Order Quantity: 2km

Packaging Details: Wooden Spool /drum

5-25days Delivery Time:

30%TT as deposit,70%Balance before • Payment Terms:

shipping.

1000km Supply Ability:



Product Specification

MODEL: GJXH-1G657A Applications: Indoor Ftth Cabling

Steel: 0.45mm • Fiber Count: 1-4 Fibers • Cable Weight: 32KG±1KG • Construction: 2pcs Steels OR FRP

> Fiber Optic Cable GJXH, Drop Fiber Optic Cable 1 Core FTTH Drop Fiber Cable GJXH



More Images

• Highlight:



Product Description

FTTH DROP Fiber Optic CABLE GJXH 1 Core

The fiber optic drop cable (indoor wiring) used for Fiber Optic Drop Cable access is centered on the optical communication unit (optical fiber), and two non-metallic reinforcements (FRP) or metal reinforcements are placed in parallel on both sides,


and finally black or colored PVC is extruded Vinyl (PVC)/Low Smoke Zero Halogen (LSZH) sheath.

cable structure
1. STEEL WIRE 2.FIBER 3. LSZH JACKAGE diameter of cable: (2.0±0.2)X(5.0±0.2)mm type fiber:Singlemode G.657A 2KM/PLYWOOD REEL REEL SIZE: 40*40*37cm G.W.: 42KG/REEL 2KM/REEL 20KG/KM

Phosphating steel wire :1 *1.0 mm Phosphating steel wire: 2*0.45 mm

Our Product Introduction







PRINTING ON SHEATH: CABLEPULS 2024 FTTH DROP CABLE XXCORE(G.657A) XXXXm

*The marking is printed every 1 meter;

• The color of marking is white, but if the remarking is necessary,

the yellow color marking shall be printed newly on a different position.

- An occasional unclear of length marking is permitted if both of the neighboring markings are clear;
- \bullet The both cable ends are sealed with heat shrinkable end caps to prevent water ingress.

| Cable Type | Fiber Count | Cable Size | Kg/km | Tensile Strength Long/Short term N |
|---------------|----------------|-----------------|-------|--|
| GJXH-1 | 1 | 2.0*3.0±0. 2 | 9.0 | 40/80 |
| GJXH-2 | 2 | 2.0*3.0±0. 2 | 9.0 | 40/80 |
| GJXH-4 | 4 | 2.0*3.0±0. 2 | 9.0 | 40/80 |
| GJXH-6 | 6 | 2.0*3.0±0. 2 | 9.0 | 40/80 |
| GJXH-8 | 8 | 2.5*3.5±0. 2 | 11.0 | 40/80 |
| GJXH-12 | 12 | 2.5*3.5±0. | 11.0 | 40/80 |

| | Unit | Specification | | | |
|--|--|---|--|--|--|
| | G652D | G652D | | | |
| 1310n | um | 9.2±0.4 | | | |
| m | P | 5.2±0.4 | | | |
| 1550n m | μm | 10.4±0.8 | | | |
| | μm | 125.0±0.1 | | | |
| | % | ≤1.0 | | | |
| | μm | ≤0.5 | | | |
| | | 20.0 | | | |
| | μm | 245±7 | | | |
| Coating/cladding concentricity error | | | | | |
| | μm | ≤1260 | | | |
| 1310n m | db/km | ≤0.36 | | | |
| 1550n | db/km | ≤0.22 | | | |
| m | | | | | |
| | kpsi | ≥100 | | | |
| Note: Other parameters meet standard ITU-T G.652 | | | | | |
| | m 1550n m ty error 1310n m 1550n | 1310n m m 1550n m m m m m m m m m m m m m m m m m m m | | | |

Production Supplier Profile



guangzhou fiber cablepuls Co Itd

+8613687956390

cotton@fibercabl



OUR PRODUCTION CAPACITY AND QUALITY CONTROL SYSTEM





- How do I place an OEM or customized order?

 1) Send your purchase intention to our email: cotton@fibercablepuls.com

 2) Our sales team will contact you to confirm the product specification, packaging, printing, quantity, and other specific information.

 3) Sign the contract or Proforma Invoice.

 4) After receiving your deposit, we will start to arrange the production.

 5) 2 weeks before the completion of production, we will notify you to start contacting shipping.

925-926, Building B1, No. 2 Chuanghui Avenue, Yonghe Yushan InternationalGuangzhou city,Guangdong province,China