ġ.

more products please visit us on fiberoptical-cables.com

Outdoor Fiber Optic Duct Cable Single Mode GYFTY Frp 24 36 48 96 144

Basic Information

• Place of Origin: GUANGZHOU/CHINA • Brand Name: PUNAISGD/CABLEPULS ISO/CE/ROSH

 Certification: Model Number: **GYFTY** Minimum Order Quantity: 2km • Price: negotiate

Packaging Details: Wooden Spool /drum

• Delivery Time: 5-25days

30%TT as deposit,70%Balance before • Payment Terms:

shipping. 100km



Product Specification

Supply Ability:

GYFTY • Item Mode: Jacket Color: Black • Fiber Type: G.652D • Outer Jacket Material: HDPE • Cable Diameter: 12.5 Mm • Armored Type: NONE

• Application: Outdoor Duct Installation • Fiber Count: 24/48/96/144/288

• Highlight: Duct Cable 144 Core, Frp Duct Cable,

GYFTY Fiber Optic Cable



More Images



Product Description

Outdoor Fiber Optic Duct Cable Single Mode GYFTY Frp 24 36 48 96 144 Core

GYFTY fiber optic cable is a non-metallic cable used for power transmission system, excessive thunder areas and high electromagnetic interface. Its mainly application is for aerial or duct use. We supply both single mode GYFTY cable and multimode GYFTY cables. GYFTY FRP locates in the center of cores as a non-metallic strength member. The cable tubes, which are filled with filling compound, are stranded around the strength member. Then the aramid yarn is applied over water proof material, the cable is completed with a PE sheath. GYFTY cables are available from 2 core to 144 core. It is used in high-voltage area for long distance communications.











TECHNICAL DATA SHEET

Part code	GYFTY XXXF				
Number of Fibers	Unit	8/12/24/36/ 48	72	96	144
Number of fiber in tube	Nos	8/6/6/12/12	12	12	12
Number of loose tube	Nos	1/2/4/3/4	6	8	12
Number of dummy filler	Nos	4/3/1/2/1	0	0	0
Central strength member	Material	FRP	FRP	FRP	FRP+ PE Coated
Loose tube	Material	PBT			
Additional stregnth	Material	Fiberglass yarn			
Outer sheath	Material	PE	PE	PE	PE
Cable nominal Diameter	MM ±0.2	9.5	10.0	11	12.4
Cable nominal weight	Kg/Km ±5	80	89	95	108
Max. working tension	N	2100	240 0	260 0	3000
Max. crush resistance	N	2000 (Short term) / 1000 (Long term)			
Min. bending radius		At full load 20 x Cable OD (including poles) At no load 15 x Cable OD			
Temperature range		Installation -0 -> +50 Operation -10 -> +7			



Production Supplier Profile





OUR PRODUCTION CAPACITY AND QUALITY CONTROL SYSTEM



How do I place an OEM or customized order?

- Send your purchase intention to our email: cotton@fibercablepuls.com
 Our sales team will contact you to confirm the product specification, packaging, printing, quantity, and other specific information.
 Sign the contract or Proforma Invoice.
 After receiving your deposit, we will start to arrange the production.
 2 weeks before the completion of production, we will notify you to start contacting shipping.



cablepuls



+8613687956390

cotton@fibercabl

925-926, Building B1, No. 2 Chuanghui Avenue, Yonghe Yushan InternationalGuangzhou city,Guangdong province,China