

FTTH 2 Port Fiber Termination Box 86 Type Wall Mount **Enclosure**

Basic Information

. Place of Origin: **GUANGZHOU/CHINA** . Brand Name: PUNAISGD/CABLEPULS

ISO/CE/ROSH · Certification:


Model Number: FTTH FIBER PANEL BOX

• Minimum Order Quantity: 100pcs • Price: negotiate · Packaging Details: plastic • Delivery Time: 5-25days

Payment Terms: 30%TT as deposit,70%Balance before

shipping.

• Supply Ability: 10000pcs




Product Specification

FTTH FIBER PANEL BOX • Item No:

SC / UPC . Connector Types: • Factory: Yes Pc+ABS • Stripper Material:

SC/LC/ST/FC-based Connector Connector: • Highlight: FTTH Fiber Panel Box Enclosure,

2 Port Fiber Termination Box, **FTTH Fiber Termination Box**



More Images





FTTH Fiber Panel Box Enclosure ATB 2 Port Fiber Termination Box 86 Type Wall Box

Product Attributes

Item no	FTTH FIBER PANEL BOX
Connector Types	SC / UPC
Factory	Yes
Stripper Material	pc+ABS
Connector	SC/LC/ST/FC-based connector

Product Description

This FTTH Fiber Panel Box is a user-end product designed for optical fiber to desktop solutions. It provides efficient fiber access and port output for residential and commercial applications.

Ideal for home or office environments with double-core fiber access

Designed for end termination in residential buildings and villas

Perfect for FTTH indoor applications

Provides optical or data access to end users

Accommodates 2 SC adapters

Features internal storage for surplus fiber with easy operation

Optimized inner space design with proper bending radius

Effective fiber protection for FTTD (Fiber To The Desktop) systems

Compact dimensions: 86×86×25mm

Applications

Local Area Network

CATV Network

FTTX System

Wide Area Network

Data communication

Network infrastructure

Note

Fiber optic connectors not included.



Technical Specifications

Product name	86 Faceplate termination box
Material	PC+ABS
Color	White
Dimension	86×86×25mm
Suitable Adapter	SC, LC
Fiber type	SM&MM
Scope of application	3.0×2.0mm drop cable or indoor cable
Tensile strength	> 50 N
Operating temperature	-40 ~ +85°C
Mounting	Wall mount

Key Features

Dust-proof design with IP-45 protection level

Integrated splice cassette and cable management rods

Optimal fiber radius management

Easy maintenance and capacity extension

Compatible with fusion or mechanical splicing

Embedded surface design for simple installation/removal

Single port cable entrance for patch cables

Configuration

Material	Size	Max Capacity	Mounting Way	Weight	Color
PC+ABS	86×86×24mm	SC 2 Port / LC 4 Port	Wall Mounting	0.2kg	White

Production Supplier Profile





guangzhou fiber cablepuls co ltd



+8613687956390



cotton@fibercablepuls.com



fiberoptical-cables.com

925-926, Building B1, No. 2 Chuanghui Avenue, Yonghe Yushan InternationalGuangzhou city,Guangdong province,China