ġ.

more products please visit us on fiberoptical-cables.com

FTTH Fiber Panel Box Enclosure ATB 2 Port Fiber Termination Box 86 Type **Wall Box**

Basic Information

• Place of Origin: GUANGZHOU/CHINA Brand Name: PUNAISGD/CABLEPULS · Certification: ISO/CE/ROSH FTTH FIBER PANEL BOX Model Number:

 Minimum Order Quantity: 100pcs • Price: negotiate Packaging Details: plastic Delivery Time: 5-25days

30%TT as deposit,70%Balance before • Payment Terms:

shipping. 10000pcs Supply Ability:



Product Specification

FTTH FIBER PANEL BOX • Item No:

• Connector Types: SC / UPC Factory: Yes • Stripper Material: Pc+ABS

Connector: SC/LC/ST/FC-based Connector • Highlight: FTTH Fiber Panel Box Enclosure, 2 Port Fiber Termination Box. FTTH Fiber Termination Box



More Images





Product Description

Ftth Products FTTH Fiber Panel Box Enclosure ATB 2 Port Fiber Termination Box 86 Type Wall Box

- A user end product to realize optical fiber to desktop solution
- it can be used in home or working area to occomplish double-core fiber access and port output used in the end termination of residential buildings and villas, to Fix splice with pigtails.
- used in FTTH indoor application , home or working area
- Provude users with optical access or data access
- suitable for 2 pcs SC Adapters
- May store surplus fiber inside, easy for operation
 Reasonable inner space design
- Sutable bending radius
- protect optical fiber
 realize FTTD (Fiber To The Desktop) system
- Size : 86*86*25

Application: Local Area Network **CATV Network**

FTTX System Wide Area Network Data commnication Network

Note: Not Included any Fiber Optic connector



Product details

Product details					
Product name	86 Faceplate termination box				
Material	PC+ABS				
Color	White				
Dimension	86*86*25mm				
Suitable Adapter	SC,LC				
Fiber type	SM&MM				
Scope of application	3.0x2.0mm drop cable or indoor cable				
Tensile strength	> 50 N				
Operating temperature	-40 ~ +85 C				
Mounting	wall mount				
Product Keywords	ftth Outlet Box				

- Features:
 1.Dust-proof design with IP-45 Protection level.
 2.Integrated with splice cassette and cable management rods.
 3.Manage fibers in a reasonable fiber radius condition.
 4.Easy to maintain and extend the capacity.
 5.Suitable for the fusion splice or mechanical splice.
 6.Embedded type surface, easy for installation and removal.
 7.1 ports cable entrance for patch cable.

Configuration:

r			iviax Capacity		Mounting Way	Weight	Color
F	PC+ABS	A*B*C(mm) 86*86*24			Wall Mounting	0.2kg	White

Production Supplier Profile





+8613687956390

cotton@fibercabl