

GYXTC8S Fiber Optic Cable Internet 2 4 6cores Drop Ftth Outdoor Single Mode

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:

GUANGZHOU/CHINA

ISO/CE/ROSH GYXTC8S 2km negotiate

PUNAISGD/CABLEPULS

Wooden Spool /drum

shipping

100km

- 5-25 days
- Supply Ability:

Product Specification

GYXTC8S

- Type:
- Installation Method:
- Cable Type:
- Application:
- Jacket Material:
- Cable Color:
- Highlight:

Self-supporting
Figure 8
Aerial

- ΡE
- Black
- 6cores Fiber Optic Cable, Ftth Fiber Optic Cable , GYXTC8S Cable

30% TT as deposit, 70% Balance before



1

3

More Images







Product Description

GYXTC8S Fiber Optic Cable Internet 2 4 6cores Frop Ftth Outdoor Cable Single Mode **Products Description**



GYXTC8S Fiber Optic Cable

In the GYXTC8S cable, a 250µm fiber is embedded in a tube constructed from a material with a high modulus, filled with a hydrophobic compound. The tube is then encased with a plastic-coated steel strip (PSP) that runs in a longitudinal direction. To ensure the cable is compact and has longitudinal water-blocking properties, a water-blocking substance is intercalated between the steel strip and the tube. The cable also contains a steel strand that is arranged in an octagonal shape, all encapsulated within a polyethylene sheath.

Detail Images



Features:

1. The cable's steel wire strand is endowed with a very high tensile strength, facilitating overhead self-supporting installation and reducing the costs of installation.

- 2. It has good mechanical and temperature stability.
- 3. The loose tube material is inherently resistant to hydrolysis and is strong.
- 4. The tube is filled with a special grease to ensure the fiber's protection.
- 5. The double-coated steel strip (PSP) increases the cable's resistance to moisture.
- 6.It has a small diameter and is light, making it easy to lay.
- 7.It is available in long lengths and is priced at a low cost.

Product Paramenters

			_	
Fiber Model		G.652D		
Loose Tube	Material	PBT		
	Diameter (±0.1)mm	1.8	2.0	2
	Thickness (±0.05)mm	0.30		
Water Blocking layer(Material)		Water Blocking Tape		
	Material	Steel Tape		
Armoring	Thickness (±0.03)mm	0.2		
Messenger Wire	Material	Galvanized steel strand		
	Size (±0.05)mm	2.7mm		
	Material		MDPE	

Web	Size (±0.1)mm		2.0 ×3.0		
Outer	Material		MDPE		
Sheath	Thickness(±0.1)mm	1.2			
Outer	Outor Material		MDPE		
Sheath@	Thickness (±0.1)mm	1.5			
Cable Diamete	7.0* 11.5	7.0*11.5	7 3 * 1 3 5		
Cable Weigh	80	80	9 4		
	Without Tension	10.0 ×Cable-φ			
Min. bending radius	Under Maximum Tension	20.0 ×Cable-φ			
	Installation	-20~+60			
Temperature range (°C)	Transport&Stora ge	-40~+70			
	Operation	-40~+70			

Company Profile





OUR PRODUCTION CAPACITY AND QUALITY CONTROL SYSTEM



Color Fiber Testing

A Stranded Loose Tube

A Finished Cable Testing





HOT-SALE PRODUCT





FAQ

1. Why choose us?

We are manufacturer, Located in Guangzhou, China, started from 2011, sell to Domestic Market(100.00%). There are total about 11-50 people in our factory.

2. how can we guarantee quality?

Always a pre-production sample before mass production; Always final Inspection before shipment;

3.Can you send products to my country?

Sure, we can. If you do not have your own ship forwarder, we can help you.

4. Can you do OEM for me?

We accept all OEM orders, just contact us and give me your design.we will offer you a reasonable price and make samples for you.

5. what services can we provide?

Accepted Delivery Terms: FOB,CIF,EXW Accepted Payment Currency:USD,EUR,JPY,CAD,AUD,HKD,GBP,CNY,CHF; Accepted Payment Type: T/T,L/C,D/P D/A,PayPal,Western Union,Escrow; Language Spoken:English,Chinese

	gu	angzhou fiber cablepuls	co Itd
C	+8613687956390	cotton@fibercablepuls.com	<i>iberoptical-cables.com</i>
925-926,	Building B1, No. 2 Chuang	hui Avenue, Yonghe Yushan Inter province,China	nationalGuangzhou city,Guangdong