# 1310nm / 1550nm / 1625nm OTDR Fiber Optic Tester For Wireless Lan **Network**

#### **Basic Information**

. Place of Origin: **GUANGZHOU/CHINA** . Brand Name: PUNAISGD/CABLEPULS

· Certification: ISO/CE/ROSH

Model Number: OTDR • Minimum Order Quantity: 1 piece • Price: negotiate

· Packaging Details: Wooden Spool /drum

• Delivery Time: 5-25 days

Payment Terms: 30% TT as deposit, 70% Balance before

shipping

• Supply Ability: negotiate



## **Product Specification**

Model Number: **OTDR Tester** · Origin: Guangdong Network: Wireless Lan . Selling Units: Selling Units: Insertion Loss: <0.3dB

• Weather Resistance: Suitable For Various Weather Conditions · Highlight: 1310nm/1550nm/1625nm Fiber Optic Tester, 1310nm/1550nm/1625nm OTDR fiber optic tester

, High quality Fiber Optic Tester



## More Images



## High quality factory price 1310nm/1550nm/1625nm OTDR fiber optic tester



An optical power meter (OPM) is utilized to measure the power of optical signals. Typically, this term pertains to devices assessing average power in fiber optic networks. Other light power measurement instruments are often called radiometers, photometers, laser power meters (which can be photodiode sensors or thermopile sensors), light meters, or lux meters.



#### **Feature**

Connector: 2.5mm universal interface Operating Wavelength: 850 to 1625 nm

Calibration Type: Manual

Case Design: Miniature protective case, sleek and functional

Accuracy Rating: ±0.2 dB

Measurement Scope: -70 to +6 dBm / -50 to +26 dBm Button Feature: Waterproof, designed for outdoor use Visibility: LED lights, perfect for dim conditions

### **Application**

- 1. Maintenance in Telecom
- 2. Maintenance CATV
- 3. Fiber Optic Lab Testing
- 4. Other Fiber Optic Measurements

# **PRODUCT SPECIFICATIONS**

Model	SL-NK3200
Output Power	-5dBm±0.5dB
Output Wavelength	1310/1550nm
Frequency Output	270/1k/2kHz
Wavelength Recognition	1310/1550nm
Test Range	-50~+26dBm
Resolution	0.01dB
Calibrated Wavelength	850/1300/1310/1490/1550/1625nm
Accuracy	±0.2dB
Memory Capacity	999 groups
Weight	180g
Dimension	145L×60W×45H(mm)
Communication Port	USB
Power Supply	2* Ni-MH AA battery
Optional	(PD)1.25mm adapter/2.5mm adapter

# **OUR FACTORY**













# **OUR PRODUCTION CAPACITY AND QUALITY CONTROL SYSTEM**











▲ Color Coating

▲ Color Fiber Testing

A Fiber to Loose Tube

▲ Stranded Loose Tube

▲ Finished Cable Testing



# TRANSPORT&PAY A. POSTAL SERVICE Land Transportation Air Freight Shipping Delivery































PACKAGING → TRUCK LOADING → GOODS RECEIPT



# **HOT-SALE PRODUCT**





#### **FAQ**

#### 1. Why choose us?

We are manufacturer, Located in Guangzhou, China, started from 2011, sell to Domestic Market(100.00%). There are total about 11-50 people in our factory.

#### 2. how can we guarantee quality?

Always a pre-production sample before mass production; Always final Inspection before shipment;

#### 3.Can you send products to my country?

Sure, we can. If you do not have your own ship forwarder, we can help you.

#### 4. Can you do OEM for me?

We accept all OEM orders just contact us and give me your design.we will offer you a reasonable price and make samples for you.

#### 5. what services can we provide?

Accepted Delivery Terms: FOB,CIF,EXW

Accepted Payment Currency:USD,EUR,JPY,CAD,AUD,HKD,GBP,CNY,CHF; Accepted Payment Type: T/T,L/C,D/P D/A,PayPal,Western Union,Escrow;

Language Spoken: English, Chinese









e fiberoptical-cables.com

925-926, Building B1, No. 2 Chuanghui Avenue, Yonghe Yushan InternationalGuangzhou city,Guangdong province, China