₫

Air Blown Micro Cable Factory JET 12 24 48 72 96 144 288F GCYFTY/ GCYFY **Dry Core Air Blown Fiber Optic Cable**

Basic Information

• Place of Origin: GUANGZHOU/CHINA • Brand Name: PUNAISGD/CABLEPULS Certification: ISO/CE/ROSH

 Model Number: GCYFY-36B1.3

 Minimum Order Quantity: 2km • Price: negotiate

Packaging Details: Wooden Spool /drum

Delivery Time: 5-25days

30%TT as deposit,70%Balance before • Payment Terms:

shipping. 100km



Product Specification

Supply Ability:

Model: GCYFY-36B1.3 • Item: Air Blown Micro Cable

Jacket Material: PE Sheath • Fiber Type: G.652D/G657a1

• Cable Color: Black

• Highlight: 288F Air Blown Micro Cable Dry Core Air Blown Micro Cable.

GCYFY Air Blown Micro Cable



More Images



Product Description


Air Blown Micro Cable Factory JET 12 24 48 72 96 144 288F GCYFTY/ GCYFY Dry Core Air Blown Fiber Optic Cable


Product Description

The structure of miniature JET is put 250µm single-mode or multi-mode optical fiber into a loose tube, the loose tube is made of high modulus material, which are filled with non-toxic and harmless waterproof compounds. Outside of loose tube is stranded with non-metallic reinforced element aramid, then extruded black or colored high-density polyethylene (HDPE) sheath form a cable.

Features:

- Small size and light weight
 Tube filling compound providing key protection for fibres
 Unique design of sheath with grooves ensuring good air blowing performance
 Allowing to blow by phases to reduce initial investment
 High blowing speed up to 50m/min, and long blowing distance up to 1000m
 Allowing to blow out and replace with new cables to keep technical superiority
 Allowing to cut micro ducts anywhere anytime for branch without influences on other
- cables, saving manholes, hand holes and cable joints





Characteristics

- Small overall diameter, lightweight, moderate hardness, suitable for air-blow installation.
- Non- metallic structure, no need for grounding.



TECHNICAL DATA SHEET

fiber count	CSM diameter	nomin tickne of out jacket	ess er	cabl	e dia	meter	cable weight	Bending radius
2-12	1.4/1.4	1.6	1	3.5			11	10D/20D
14-24	1.4/1.4	1.6		4.1			14	10D/20D
26-72	1.4/1.4	1.6		5.0			22	10D/20D
74-96	1.4/1.4	1.6		5.9			33	10D/20D
98-120	1.4/1.4	1.6		7.0			43	10D/20D
122-144	1.6/1.6	1.6		7.7			52	10D/20D
146-216	1.6/1.6	1.6		7.9			52	10D/20D
218-288	1.6/1.6	1.6	(9.0			72	10D/20D
Item				U	nit	Specificat	ion	
Fier Tyoe				G	652	G652D		
				n μι	m	9.2±0.4		
Mode file				,				

	1550n m	μm	10.4±0.8				
Cladding diameter		μm	125.0±0.1				
Cladding non-circularity		%	≤1.0				
Core/cladding concentricity error		μm	≤0.5				
Coating diameter		μm	245±7				
Coating/cladding concentricity error			≤12				
Cable cut-off wavelength		μm	≤1260				
Attenuation Coefficient	1310n m	db/km	≤0.36				
Attenuation Goenicient	1550n m	db/km	≤0.22				
Proof stress level		kpsi	≥100				
Note: Other parameters meet standard ITU-T G.652							

Cable Marking&Fibers Colors

- COMPANY Fiber cable name N*cores G.652D 2024 XXXXm

 *The marking is printed every 1 meter;

 ****G.652D** means ITU-T Rec. Low Water Peak (LWP) G.652 single mode optical fiber..

Also can according to client cable marking.



Production Supplier Profile












OUR PRODUCTION CAPACITY AND QUALITY CONTROL SYSTEM





How do I place an OEM or customized order?

- Send your purchase intention to our email: cotton@fibercablepuls.com
 Our sales team will contact you to confirm the product specification, packaging, printing, quantity, and other specific information.
 Sign the contract or Proforma Invoice.
 After receiving your deposit, we will start to arrange the production.
 2 weeks before the completion of production, we will notify you to start contacting shipping.

925-926, Building B1, No. 2 Chuanghui Avenue, Yonghe Yushan InternationalGuangzhou city,Guangdong province,China