



## Outdoor Armored 12 Core Single Mode GYXTW Fiber Optic Cable Price List

Our Product Introduction

for more products please visit us on [fiberoptical-cables.com](http://fiberoptical-cables.com)


### Basic Information

- Place of Origin: GUANGZHOU/CHINA
- Brand Name: PUNAISGD/CABLEPULS
- Certification: ISO/CE/ROSH
- Model Number: GYXTW-4B1.3
- Minimum Order Quantity: 2km
- Price: negotiate
- Packaging Details: Wooden Spool /drum
- Delivery Time: 5-25days
- Payment Terms: 30%TT as deposit,70%Balance before shipping.
- Supply Ability: 100km



### Product Specification

- Model No: GYXTW-4B1.3
- Use: Aerial
- Loose Tube Material: PBT With Jelly
- Cable Diameter: 6mm 7mm 8mm
- Samples: Free
- Fiber Grade: G652D/ G657A1
- Waterblocking Material: Water Blocking Tape Or Filling Compound
- Steel Wire: 0.7\*2mm/1\*2mm
- Cable Color: Black
- Highlight: Outdoor Armored Fiber Optic Cable,  
12 Core Fiber Optic Cable,  
Single mode Fiber Optic Cable



### More Images



### Product Description


#### Outdoor Fiber Optic Cable Outdoor Armored 12 Core Single mode GYXTW Fiber Optic Cable Price List

GYXTW fiber optic cable is constructed using high-quality materials for durability and performance. The loose tube is made of hydrolysis-resistant material filled with a special water-blocking gel to protect the fibers. Two parallel steel wires are embedded for tensile strength, while a PE sheath provides UV and environmental protection. Additionally, the cable is reinforced with steel tape to improve moisture resistance.

GYXTW cables are known for their excellent mechanical and temperature resistance. The loose tube structure prevents damage from environmental factors, while the steel wires enhance tensile strength, making the cable ideal for long-distance installations. The combination of water-blocking gel and steel tape ensures superior moisture protection, giving the cable durability in harsh conditions.

Due to its robust design and features, GYXTW is commonly used in outdoor environments, especially for duct and aerial installations. Its tensile strength and moisture resistance make it suitable for applications where cables may face physical stress or exposure to water. This cable is widely used in telecom networks, offering reliable data transmission over long distances.

Our Product Introduction



## APPLICATION



Smart TV



Computer



Notebook



Router



Printer



CCTV




Switch



Switchboard

## GYXTW Cable Place Order Information




## Cable data

Fiber count	Structure	Fibers per tube	Loose tube diameter (mm)	CSM diameter/pad diameter (mm)	Nominal Thickness of outer jacket (mm)	Cable diameter/Height (mm)	Cable weight (kg/km)
2	1	2	1.7±0.1	1.0/1.0	1.6	8.0±0.2	57
4	1	4	1.85±0.1	1.0/1.0	1.6	8.0±0.2	58
6	1	6	1.9±0.1	1.0/1.0	1.6	8.0±0.2	58
8	1	8	2.0±0.1	1.0/1.0	1.6	8.0±0.2	60
12	1	12	2.2±0.1	1.0/1.0	1.6	8.0±0.2	60

## Fiber Parameters

No.	Items	Unit	Specification
1	Mode Field Diameter	1310nm	9.2±0.4
		1550nm	10.4±0.8
2	Cladding Diameter	μm	125.0±1.0
3	Cladding Non-Circularity	%	≤1.0
4	Core-Cladding Concentricity Error	μm	≤0.5

5	Coating Diameter		μm	245±5
6	Coating Non-Circularity		%	≤6.0
7	Cladding-Coating Concentricity Error		μm	≤12.0
8	Cable Cutoff Wavelength		nm	λ <sub>cc</sub> ≤1260
9	Attenuation(max.)	1310nm	dB/km	≤0.35
		1550nm	dB/km	≤0.21
		1380nm	dB/km	≤0.35
		1625nm	dB/km	≤0.24
10	Attenuation and wavelength	1310nm 1285-1330nm	dB/km	≤0.04
		1550nm 1525-1575nm	dB/km	≤0.03
		1550nm 1480-1580nm	dB/km	≤0.05
11	Dispersion	1288-1339nm	ps/(nm.km)	≥-3.5, ≤3.5
		1271-1360nm	ps/(nm.km)	≥-5.3, ≤5.3
		1480-1580nm	ps/(nm.km)	≤20
		1550nm	ps/(nm.km)	≤18
12	Zero dispersion wavelength		Nm	1300-1324
13	Zero dispersion slope		ps/(nm <sup>2</sup> ·km)	≤0.092
14	Typical value		ps/(nm <sup>2</sup> ·km)	0.04
15	Largest individual fiber		Ps/√ km	0.2
16	Link design values		Ps/√ km	0.1
17	Two way average		1310nm-1550	≤0.01dB




**Cable Marking&Fibers Colors**  
COMPANY Fiber cable name N\*cores G.652D 2024 XXXXm

\*The marking is printed every 1 meter;  
\*\*\*G.652D\* means ITU-T Rec. Low Water Peak (LWP) G.652 single mode optical fiber..


Also can according to client cable marking.



### Production Supplier Profile



## COMPANY PROFILE



### ABOUT FIBER

Guangzhou fiber cablepuls co.,ltd

Fiber cablepuls is one of the high-tech fiber optic cable factories in China that can produce the most complete series of fiber optic cables, equipped with the most advanced fiber optic cable manufacturing, and have the most advanced fiber optic connector production and testing equipment in China.

The factory has obtained SGS ISO9001-2015, ISO14001-2004 and GB/T28001-2001 successfully obtained international system certification.

Over the past 12 years, we have provided optical cable products and comprehensive solutions to more than 90 countries and regions around the world, and have received unanimous praise from customers, such as foreign telecom departments of the United States, Mexico Telecom, Thailand Telecom, Philippines Telecom, etc.; domestic customers include: China Mobile, the General Administration of Radio, Film and Television, Lenovo, and many other large national enterprises.



### OUR PRODUCTION CAPACITY AND QUALITY CONTROL SYSTEM



#### How do I place an OEM or customized order?

- 1) Send your purchase intention to our email: [cotton@fibercablepuls.com](mailto:cotton@fibercablepuls.com)
- 2) Our sales team will contact you to confirm the product specification, packaging, printing, quantity, and other specific information.
- 3) Sign the contract or Proforma Invoice.
- 4) After receiving your deposit, we will start to arrange the production.
- 5) 2 weeks before the completion of production, we will notify you to start contacting shipping.

925-926, Building B1, No. 2 Chuanghui Avenue, Yonghe Yushan International Guangzhou city, Guangdong province, China