



Fiberglass Reinforced Plastic Rod FRP Central Member FRP Strength

Basic Information

- Place of Origin: GUANGZHOU
- Brand Name: PUNAISGD
- Model Number: frp 0.8mm
- Minimum Order Quantity: 10km
- Price: negotiate
- Packaging Details: Spool
- Delivery Time: 7DAYS
- Payment Terms: T/T
- Supply Ability: 100000KM



Product Specification

- Highlight: **FRP Central Member,
Fiberglass Reinforced FRP Central Member**

Product packaging



Product Description

Fiberglass reinforced plastic rod, FRP central member, FRP strength:

Product Description

1.Specification: 1.0mm(diameter)

2. Features: 1) not sensitive to the lightning strike, applied to the areas which are common with frequent lightning and rain;

2) Not obstructed by induced current and can be installed close to the power unit and device;

3) No harmful gas that would affect the optical transmission indicators;

4) Has the characteristics of high tensile and light weight;

5) bullet-proof, ant-proof and anti-tooth proof.

3. FRP technical performance indicators:

Property	Values
Tensile strength (Mpa)	≥ 1100
Tensile modulus (Gpa)	≥ 50
Flexural strength (Mpa)	≥ 1100
Flexural modulus (Gpa)	≥ 50
Elongation at break (%)	≤ 4
Coefficient of linear thermal expansion (-30-80°C) (1/°C)	$< 8 \times 10^{-6}$
Diameter tolerance (mm)	$\pm 2\%$
Density (g/cm ³)	2.05~2.15
Minimum bending radius (mm)	40×D
High temperature bending test (50D,100°C,120h)	No bur, cracks and break

Packaging & Shipping

Common: 25km/roll at least

Special: We can produce non-standard diameter and length to meet customers' requirements.

Product packaging



guangzhou fiber cablepuls co ltd



+8613687956390



cotton@fibercablepuls.com



fiberoptical-cables.com

925-926, Building B1, No. 2 Chuanghui Avenue, Yonghe Yushan InternationalGuangzhou city,Guangdong province,China