



ADSS Fiber Optic Cable 300M Span Single Mode Aerial Installation

Basic Information

- Place of Origin: GUANGZHOU/CHINA
- Brand Name: PUNAISGD/CABLEPULS
- Certification: ISO/CE/ROSH
- Model Number: ADSS-12/24/48b1.3-SJ-100M
- Minimum Order Quantity: 2km
- Price: negotiate
- Packaging Details: Wooden Spool $\Phi 1200 \times 750$ mm
- Delivery Time: 5-25days
- Payment Terms: 30%TT as deposit, 70%Balance before shipping.
- Supply Ability: 100km




Product Specification

- Type: ADSS Optical Cable-12/24/48b1.3-100m
- Fiber Type: Single Mode
- Fiber Count: 6/12/24/36/48/72/96/144
- Outer Sheath: Black PE
- Inner Sheath Material: PE/AT
- Installation Method: Aerial
- Strength Member Material: FRP/ARMID YARN
- Cable Diameter: 12.5mm
- Highlight: Double Jackets ADSS Fiber Optic Cable, 300M Span ADSS Fiber Optic Cable, Self Supporting ADSS Fiber Optic Cable



More Images



Product Description

ADSS Fiber Optic Cable 300M Span All Dielectric Self-Supporting Double Jackets Optical Fiber Cable

Product Specifications

Attribute	Value
Type	ADSS optical cable-12/24/48b1.3-100m
Fiber Type	Single mode
Fiber Count	6/12/24/36/48/72/96/144
Outer Sheath	Black PE
Inner Sheath Material	PE/AT
Installation Method	Aerial
Strength Member Material	FRP/ARMID YARN
Cable Diameter	12.5mm

Product Overview

The ADSS-300M Span All Dielectric Self-Supporting Double Jackets Optical Fiber Cable is designed for high-performance telecommunications applications.

Applications

- Outdoor aerial self-supporting installation
- Long-distance communication and local trunk lines
- CATV & computer networks systems
- Telecom or outside plant campus backbone applications
- Ethernet LAN Network, CCTV, Network Camera, PLC
- Electric utility distribution power lines
- Fiber-to-the-X networks
- Mechanically rugged design for aerial and underground duct applications



- Coated Optical Fiber
- Filling Gel
- PBT Loose Tube
- FRP Strengthen Member
- Filling Compound
- Filler
- Aramid yarn
- PE Outer Jacket

ADSS-SJ



- Optical Fiber
- Gel filling compound
- PBT Loose Tube
- FRP Strengthen Member
- Inner sheath
- Aramid yarn
- Outer Jacket

ADSS-DJ

Ordering Information

Fiber count	Structure	Fibers per tube	Loose tube diameter (mm)	CSM diameter/pad diameter (mm)	Nominal Thickness of outer jacket (mm)	Cable diameter/Height (mm)	Cable weight (kg/km)
-------------	-----------	-----------------	--------------------------	--------------------------------	--	----------------------------	----------------------

4	1+6	4	1.9±0.1	2.0/2.0	1.6	9.5±0.2	80
6	1+6	6	2.0±0.1	2.0/2.0	1.6	9.8±0.3	80
8	1+6	4	1.9±0.1	2.0/2.0	1.6	9.8±0.3	80
12	1+6	6	2.1±0.1	2.0/2.0	1.6	9.8±0.3	80
24	1+6	12	2.1±0.1	2.0/2.0	1.6	9.8±0.3	80
36	1+6	12	2.2±0.1	2.0/2.0	1.6	10.0±0.3	85
48	1+6	12	2.2±0.1	2.0/2.0	1.6	10.0±0.3	85
72	1+6	12	2.2±0.1	2.0/2.0	1.6	10.0±0.3	85
96	1+8	12	2.2±0.1	2.0/3.4	1.7	11.8±0.3	123
144	1+12	12	2.2±0.1	3.0/6.2	1.7	14.5±0.3	175

Fiber Parameters (G.652D)

No.	Items	Unit	Specification
1	Mode Field Diameter (1310nm)	μm	9.2±0.4
1	Mode Field Diameter (1550nm)	μm	10.4±0.8
2	Cladding Diameter	μm	125.0±1.0
3	Cladding Non-Circularity	%	≤1.0
4	Core-Cladding Concentricity Error	μm	≤0.5
5	Coating Diameter	μm	245±5
6	Coating Non-Circularity	%	≤6.0
7	Cladding-Coating Concentricity Error	μm	≤12.0
8	Cable Cutoff Wavelength	nm	λ _{cc} ≤1260
9	Attenuation(max.) (1310nm)	dB/km	≤0.35
9	Attenuation(max.) (1550nm)	dB/km	≤0.21
9	Attenuation(max.) (1380nm)	dB/km	≤0.35
9	Attenuation(max.) (1625nm)	dB/km	≤0.24
10	Attenuation and wavelength (1310nm 1285-1330nm)	dB/km	≤0.04
10	Attenuation and wavelength (1550nm 1525-1575nm)	dB/km	≤0.03
10	Attenuation and wavelength (1550nm 1480-1580nm)	dB/km	≤0.05
11	Dispersion (1288-1339nm)	ps/(nm.km)	≥-3.5, ≤3.5
11	Dispersion (1271-1360nm)	ps/(nm.km)	≥-5.3, ≤5.3
11	Dispersion (1480-1580nm)	ps/(nm.km)	≤20
11	Dispersion (1550nm)	ps/(nm.km)	≤18
12	Zero dispersion wavelength	Nm	1300-1324
13	Zero dispersion slope	ps/(nm ² •km)	≤0.092
14	Typical value	ps/(nm ² •km)	0.04
15	Largest individual fiber	Ps/√ km	0.2
16	Link design values	Ps/√ km	0.1
17	Two way average (1310nm-1550)	dB	≤0.01

Key Benefits

Dielectric design eliminates the need for metal support structures, reducing installation costs

Withstands high electric fields and performs reliably near high-voltage power lines without electromagnetic interference

Superior weather resistance and tensile strength for harsh environments including coastal areas and high altitudes



Application Examples



Optical Fiber Hardware for ADSS Cables



How to Place an Order

Send your purchase intention to our email: cotton@fibercablepuls.com

Our sales team will contact you to confirm product specifications, packaging, printing, quantity, and other requirements

Sign the contract or Proforma Invoice

After receiving your deposit, we will arrange production

Two weeks before production completion, we will notify you to arrange shipping



guangzhou fiber cablepuls co ltd



+8613687956390



cotton@fibercablepuls.com



fiberoptical-cables.com

925-926, Building B1, No. 2 Chuanghui Avenue, Yonghe Yushan International Guangzhou city, Guangdong province, China