



ADSS Fiber Optic Cable 6-144 Cores Aerial Single Mode PE Sheath

Basic Information

- Place of Origin: GUANGZHOU/CHINA
- Brand Name: PUNAISGD/CABLEPULS
- Certification: ISO/CE/ROSH
- Model Number: ADSS-12/24/48b1.3-SJ-100M
- Minimum Order Quantity: 2km
- Price: negotiate
- Packaging Details: Wooden Spool Φ1200*750mm
- Delivery Time: 5-25days
- Payment Terms: 30%TT as deposit,70%Balance before shipping.
- Supply Ability: 100km




Product Specification

- Type: ADSS Optical Cable-12/24/48b1.3-100m
- Fiber Type: Single Mode
- Fiber Count: 6/12/24/36/48/72/96/144
- Outer Sheath: Black PE
- Inner Sheath Material: PE/AT
- Installation Method: Aerial
- Strength Member Material: FRP/ARMID YARN
- Cable Diameter: 12.5mm
- Highlight: 6 Cores ADSS Fiber Optic Cable,
Manufacturer ADSS Fiber Optic Cable,
144 Cores ADSS Fiber Optic Cable



More Images



Product Description

ADSS Fiber Optic Cable 6 To 144 Cores

Product Specifications

Attribute	Value
Type	ADSS optical cable-12/24/48b1.3-100m
Fiber Type	Single mode
Fiber Count	6/12/24/36/48/72/96/144
Outer Sheath	Black PE
Inner Sheath Material	PE/AT
Installation Method	Aerial
Strength Member Material	FRP/ARMID YARN
Cable Diameter	12.5mm

ADSS fiber optic cables (All Dielectric Self Supported) are designed for aerial installation between poles, eliminating the need for a messenger wire. These cables provide necessary tensile strength through aramid material, which offers excellent mechanical properties at minimal weight.





Ordering Information

Fiber count	Structure	Fibers per tube	Loose tube diameter (mm)	CSM diameter/pad diameter (mm)	Nominal Thickness of outer jacket (mm)	Cable diameter/Height (mm)	Cable weight (kg/km)
4	1+6	4	1.9±0.1	2.0/2.0	1.6	9.5±0.2	80
6	1+6	6	2.0±0.1	2.0/2.0	1.6	9.8±0.3	80
8	1+6	4	1.9±0.1	2.0/2.0	1.6	9.8±0.3	80
12	1+6	6	2.1±0.1	2.0/2.0	1.6	9.8±0.3	80
24	1+6	12	2.1±0.1	2.0/2.0	1.6	9.8±0.3	80
36	1+6	12	2.2±0.1	2.0/2.0	1.6	10.0±0.3	85
48	1+6	12	2.2±0.1	2.0/2.0	1.6	10.0±0.3	85
72	1+6	12	2.2±0.1	2.0/2.0	1.6	10.0±0.3	85
96	1+8	12	2.2±0.1	2.0/3.4	1.7	11.8±0.3	123
144	1+12	12	2.2±0.1	3.0/6.2	1.7	14.5±0.3	175

Fiber Parameters (G.652D)

No.	Items	Unit	Specification
1	Mode Field Diameter (1310nm/1550nm)	μm	9.2±0.4 / 10.4±0.8
2	Cladding Diameter	μm	125.0±1.0
3	Cladding Non-Circularity	%	≤1.0
4	Core-Cladding Concentricity Error	μm	≤0.5
5	Coating Diameter	μm	245±5

6	Coating Non-Circularity	%	≤ 6.0
7	Cladding-Coating Concentricity Error	μm	≤ 12.0
8	Cable Cutoff Wavelength	nm	$\lambda_{cc} \leq 1260$
9	Attenuation(max.) at various wavelengths	dB/km	1310nm: ≤ 0.35 , 1550nm: ≤ 0.21 , 1380nm: ≤ 0.35 , 1625nm: ≤ 0.24

Key Benefits

Dielectric design eliminates metal support structures, reducing installation costs

Withstands high electric fields for reliable performance near high-voltage power lines

Superior weather resistance and tensile strength for harsh environments

Long-term performance in coastal areas and high altitudes



Applications





Optical Fiber Hardware



Ordering Process

Send purchase intention to cotton@fibercablepuls.com

Our sales team will confirm product specifications and requirements

Sign contract or Proforma Invoice

Production begins after deposit receipt

Shipping coordination begins 2 weeks before production completion



guangzhou fiber cablepuls co ltd



+8613687956390



cotton@fibercablepuls.com



fiberoptical-cables.com

925-926, Building B1, No. 2 Chuanghui Avenue, Yonghe Yushan International Guangzhou city, Guangdong province, China