



Outdoor Fiber Optic Cable Single Mode Central Loose Tube GYXTW Optic Fiber Cable

Our Product Introduction

for more products please visit us on fiberoptical-cables.com

Basic Information

- Place of Origin: GUANGZHOU/CHINA
- Brand Name: PUNAISGD/CABLEPULS
- Certification: ISO/CE/ROSH
- Model Number: GYXTW-8B1.3
- Minimum Order Quantity: 2km
- Price: negotiate
- Packaging Details: Wooden Spool /drum
- Delivery Time: 5-25days
- Payment Terms: 30%TT as deposit,70%Balance before shipping.
- Supply Ability: 100km



Product Specification

- Model No: GYXTW-8/12B1.3
- Use: Aerial/overhead
- Loose Tube Material: PBT With Jelly
- Cable Diameter: 8mm
- Samples: Free
- Fiber Grade: G652D
- Waterblocking Material: Water Blocking Tape Or Filling Compound
- Steel Wire: 1.0*2mm
- Cable Color: Black
- Highlight: Central Loose Tube Optic Fiber Cable, GYXTW Optic Fiber Cable Single Mode, Outdoor Fiber Optic Cable Single Mode



Product Description

Outdoor Fiber Optic Cable Single Mode Central Loose Tube GYXTW Optic Fiber Cable


Description:

1. Single jelly compound filled loose tube containing up to 24 fibers
2. Waterproof tape between the steel tape and loose tube with jelly compound.
3. Double coated PE corrugated steel tape under PE sheath.
4. Parallel double steel wire as strength member.
5. Compact structure, light weight, steel tape armored excellent water-proof layer, good moisture.

General Specifications:

Cable Type	Central Loose Tube fiber optic cable GYXTW
Fiber Type	SM G.652D
Application	Long-distance communication, LAN
Recommended installation methods	Aerial
Environment	Outdoor


Our Product Introduction



APPLICATION



GYXTW Cable Place Order Information




Cable data

Fiber count	Structure	Fibers per tube	Loose tube diameter (mm)	CSM diameter/pad diameter (mm)	Nominal Thickness of outer jacket (mm)	Cable diameter/Height (mm)	Cable weight (kg/km)
2	1	2	1.7±0.1	1.0/1.0	1.6	8.0±0.2	57
4	1	4	1.85±0.1	1.0/1.0	1.6	8.0±0.2	58
6	1	6	1.9±0.1	1.0/1.0	1.6	8.0±0.2	58
8	1	8	2.0±0.1	1.0/1.0	1.6	8.0±0.2	60
12	1	12	2.2±0.1	1.0/1.0	1.6	8.0±0.2	60

Fiber Parameters

No.	Items	Unit	Specification
			G.652D
1	Mode Field Diameter	1310nm 1550nm	μm 9.2±0.4 10.4±0.8
2	Cladding Diameter	μm	125.0±1.0
3	Cladding Non-Circularity	%	≤1.0

4	Core-Cladding Concentricity Error	μm	≤0.5
5	Coating Diameter	μm	245±5
6	Coating Non-Circularity	%	≤6.0
7	Cladding-Coating Concentricity Error	μm	≤12.0
8	Cable Cutoff Wavelength	nm	λ _{cc} ≤1260
9	Attenuation(max.)	1310nm	dB/km
		1550nm	dB/km
		1380nm	dB/km
		1625nm	dB/km
10	Attenuation and wavelength	1310nm 1285-1330nm	dB/km
		1550nm 1525-1575nm	dB/km
		1550nm 1480-1580nm	dB/km
11	Dispersion	1288-1339nm	ps/(nm.km)
		1271-1360nm	ps/(nm.km)
		1480-1580nm	ps/(nm.km)
		1550nm	ps/(nm.km)
12	Zero dispersion wavelength	Nm	1300-1324
13	Zero dispersion slope	ps/(nm ² ·km)	≤0.092
14	Typical value	ps/(nm ² ·km)	0.04
15	Largest individual fiber	Ps/√ km	0.2
16	Link design values	Ps/√ km	0.1
17	Two way average	1310nm-1550	≤0.01dB




Cable Marking&Fibers Colors
COMPANY Fiber cable name N*cores G.652D 2024 XXXXm

*The marking is printed every 1 meter;
***G.652D* means ITU-T Rec. Low Water Peak (LWP) G.652 single mode optical fiber..

Also can according to client cable marking.



Production Supplier Profile



COMPANY PROFILE



ABOUT FIBER

Guangzhou fiber cablepuls co.,ltd

Fiber cablepuls is one of the high-tech fiber optic cable factories in China that can produce the most complete series of fiber optic cables, equipped with the most advanced fiber optic cable manufacturing, and have the most advanced fiber optic connector production and testing equipment in China.

The factory has obtained SGS ISO9001-2015, ISO14001-2004 and GB/T28001-2001 successfully obtained international system certification.

Over the past 12 years, we have provided optical cable products and comprehensive solutions to more than 90 countries and regions around the world, and have received unanimous praise from customers, such as foreign telecom departments of the United States, Mexico Telecom, Thailand Telecom, Philippines Telecom, etc.; domestic customers include: China Mobile, the General Administration of Radio, Film and Television, Lenovo, and many other large national enterprises.



OUR PRODUCTION CAPACITY AND QUALITY CONTROL SYSTEM



How do I place an OEM or customized order?

- 1) Send your purchase intention to our email: cotton@fibercablepuls.com
- 2) Our sales team will contact you to confirm the product specification, packaging, printing, quantity, and other specific information.
- 3) Sign the contract or Proforma Invoice.
- 4) After receiving your deposit, we will start to arrange the production.
- 5) 2 weeks before the completion of production, we will notify you to start contacting shipping.

925-926, Building B1, No. 2 Chuanghui Avenue, Yonghe Yushan International Guangzhou city, Guangdong province, China