



Anti Rodent Fiber Optic Cable High-Performance 72CORE GYTA33 Fiber Optic Wire Outdoor G652D Communication Cables For Direct Burial

Our Product Introduction

Basic Information

- Place of Origin: GUANGZHOU/CHINA
- Brand Name: PUNAISGD
- Certification: ISO/CE/ROSH
- Model Number: GYTA33-48B1.3
- Minimum Order Quantity: 2km
- Price: negotiate
- Packaging Details: Wooden Spool /drum
- Delivery Time: 5-25days
- Payment Terms: 30%TT as deposit,70%Balance before shipping.
- Supply Ability: 100km



Product Specification

- Item No: GYFTY33-24B1.3/12B1.3
- Rodent Protection: Steel Wires Around
- Jacket Color: Black PE
- Fiber Type: G.652D
- Application: Underwater Display
- Armored: Steel Wires Around
- Highlight: **Outdoor Anti Rodent Fiber Optic Cable,
Anti Rodent Fiber Optic Cable**



for more products please visit us on fiberoptical-cables.com

Product Description



High-Performance 72CORE GYTA33 Fiber Optic Wire Outdoor G652D Communication Cables for Direct Burial

The GYTA33 is a steel-wire armored, loose tube fiber optic cable, designed for harsh environments such as underwater (rivers, lakes, shallow seas) and direct burial applications. Its robust construction ensures resistance to tension, pressure, and corrosion while maintaining stable optical performance.

The GYTA33 is a high-strength, armored fiber optic cable optimized for shallow water and direct burial applications. Its double-layer steel armor, waterproof design, and corrosion-resistant sheath make it ideal for rivers, lakes, and coastal areas, but not for deep-sea deployments, where specialized submarine cables are required.

GYTA33 Cable Place Order Information

Product display





CABLE DATA

Fiber Count	Structure	Diameter (mm)	Weight (kg/km)	Tensile(N)		Crush(N)		Bending Radius(mm)	
				Long term	Short term	Long term	Short term	Static	Dynamic
2-30	1+5	12.8	268	4000	10000	3000	5000	12.5D	25D
32-36	1+6	13.2	287	4000	10000	3000	5000	12.5D	25D
38-60	1+5	13.9	318	4000	10000	3000	5000	12.5D	25D
62-72	1+6	14.2	334	4000	10000	3000	5000	12.5D	25D
74-84	1+7	15.1	363	4000	10000	3000	5000	12.5D	25D
86-96	1+8	15.8	387	4000	10000	3000	5000	12.5D	25D
98-108	1+9	16.6	437	4000	10000	3000	5000	12.5D	25D
110-120	1+10	17.2	465	4000	10000	3000	5000	12.5D	25D
122-132	1+11	18.3	558	4000	10000	3000	5000	12.5D	25D
134-144	1+12	18.9	583	4000	10000	3000	5000	12.5D	25D
146-216	1+6+12	18.4	503	4000	10000	3000	5000	12.5D	25D
218-288	1+9+15	20.5	600	4000	10000	3000	5000	12.5D	25D

Fiber Parameters

No.	Items		Unit	Specification
				G.652D
1	Mode Field Diameter	1310nm	μm	9.2±0.4
		1550nm	μm	10.4±0.8
2	Cladding Diameter		μm	125.0±1.0
3	Cladding Non-Circularity		%	≤1.0
4	Core-Cladding Concentricity Error		μm	≤0.5
5	Coating Diameter		μm	245±5
6	Coating Non-Circularity		%	≤6.0
7	Cladding-Coating Concentricity Error		μm	≤12.0
8	Cable Cutoff Wavelength		nm	λ _{cc} ≤1260
9	Attenuation(max.)	1310nm	dB/km	≤0.35
		1550nm	dB/km	≤0.21
		1380nm	dB/km	≤0.35
		1625nm	dB/km	≤0.24
10	Attenuation and wavelength	1310nm 1285-1330nm	dB/km	≤0.04
		1550nm 1525-1575nm	dB/km	≤0.03
		1550nm 1480-1580nm	dB/km	≤0.05
11	Dispersion	1288-1339nm	ps/(nm.km)	≥-3.5, ≤3.5
		1271-1360nm	ps/(nm.km)	≥-5.3, ≤5.3
		1480-1580nm	ps/(nm.km)	≤20
		1550nm	ps/(nm.km)	≤18
12	Zero dispersion wavelength		Nm	1300-1324
13	Zero dispersion slope		ps/(nm ² •km)	≤0.092
14	Typical value		ps/(nm ² •km)	0.04
15	Largest individual fiber		Ps/√ km	0.2
16	Link design values		Ps/√ km	0.1
17	Two way average		1310nm-1550	≤0.01dB

Production Supplier Profile

COMPANY PROFILE

ABOUT FIBER

Guangzhou fiber cablepuls co.,ltd

Fiber cablepuls is one of the high-tech fiber optic cable factories in China that can produce the most complete series of fiber optic cables, equipped with the most advanced fiber optic cable manufacturing, and have the most advanced fiber optic connector production and testing equipment in China.

The factory has obtained SGS ISO9001-2015, ISO14001-2004 and GB/T28001-2001 successively obtained international system certification.

Over the past 12 years, we have provided optical cable products and comprehensive solutions to more than 90 countries and regions around the world, and have received unanimous praise from customers, such as foreign telecom departments of the United States, Mexico Telecom, Thailand Telecom, Philippines Telecom, etc.; domestic customers include: China Mobile, the General Administration of Radio, Film and Television, Lenovo, and many other large national enterprises.



OUR PRODUCTION CAPACITY AND QUALITY CONTROL SYSTEM



How do I place an OEM or customized order?

- 1) Send your purchase intention to our email: cotton@fibercablepuls.com
- 2) Our sales team will contact you to confirm the product specification, packaging, printing, quantity, and other specific information.
- 3) Sign the contract or Proforma Invoice.
- 4) After receiving your deposit, we will start to arrange the production.
- 5) 2 weeks before the completion of production, we will notify you to start contacting shipping.



guangzhou fiber cablepuls co ltd



+8613687956390



cotton@fibercablepuls.com



fiberoptical-cables.com

925-926, Building B1, No. 2 Chuanghui Avenue, Yonghe Yushan InternationalGuangzhou city,Guangdong
province,China